CICRP-300HA Mini Mullion Mount Proximity Reader


The Continental Access Mullion Pyramid Proximity Reader sets the electronic security benchmark for 125-kHz proximity readers, cards, and tags. Based upon proven contactless digital radio frequency identification (RFID) technology, Pyramid readers interface with a wide range of electronic access control systems by complying with the Wiegand communication protocol. They offer value-add features such as MAXSecure[™] and fleaPower[™], and can be ordered to support several proximity card and tag technologies. Additionally, Pyramid cards and tags are passive devices, eliminate maintenance by requiring no battery, and can be ordered to support several proximity reader technologies.



Specifications



CICRP-300HA



specifications	
Technology	Proximity
Frequency	125 kHz
Mounting	Mullions, including metal door and window frames, as well as flat surfaces
Dimensions	1.7" W × 3.2" H × 0.7" D (43 mm × 81 mm × 18 mm)
OEM Label Area Dimensions	0.9" W × 0.35" H (22.86 mm × 8.89 mm) with corner radius of 0.06" (1.5 mm)
Weight	3 oz (85 g)
Certifications	FCC, ICC, CE, C-Tick, UL Standard 294
IP Code	IP67
Voltage	+5 – 16 VDC
Current Draw	30 mA typical, 75 mA peak @ 12 VDC
Read Range	Up to 5 inches (126 mm)
Cabling	24 AWG minimum, multiconductor stranded with an overall foil shield
Interface	Wiegand ABA Track II
Operating Temperature	–40° F to 149° F (–40° C to +65° C)
Color Options	Black and a white snap-on cover included standard
Audio Tone	Beeper included standard
Indoor & Outdoor Installation	Electronics sealed in weather- and tamper-resistant epoxy potting
Warranty	Limited lifetime warranty
LED	Four-state standard (red, green, amber, and off)
	Pyramid + certain HID [®] 125-kHz Proximity protocols +

certain AWID® 125-kHz Proximity





MAXSecure[™] Unique Security Feature



FleaPower™ Energy Conservation Technology





ETL Listed Independently Tested and Certified to Conform to UL Standard 294



Warranty Lifetime Warranty



Weigand **Output Inerface**



Mullion Mount Metal Door, Window Frames & Flat Surfaces



Technologies Supported

Continental Access, a division of Napco Security Technologies, Inc. 355 Bayview Ave., Amityville, NY 11701 1.800.645.9445 631.842.9400 Fax 631.842.9135 www.cicaccess.com

Pyramid Series Proximity®, Delta®, Ranger®, and CONEKT® are the registered U.S. trademarks of Farpointe Data, Inc. AWID is a registered trademark of Applied Wireless Identifications Group. HID, the HID logo, ProxCard II, ISOProx, and ProxKey are registered trademarks of HID Global Corporation, an ASSA ABLOY company. All other trademarks are the property of their respective owners. © 8.2021 A799